

MERLEX STUCCO, INC.  
2911 ORANGE-OLIVE RD.  
ORANGE, CA 92665  
714-637-1700  
714-637-4865 FAX

MATERIAL SAFETY DATA SHEET

SECTION 1. NAME

MATERIAL NAME: BOLT GRIP

HMIS

HEALTH 1  
FIRE 0  
REACTIVITY 0  
PPE X

SECTION 2. INGREDIENTS

	weight	ACGIH TLV (a)	OSHA PEL
Silica, crystalline quartz (CAS 14808-60-7)	45-50	0.1 mg/ m <sup>3</sup> (respirable)	(b)
Calcium Hydroxide (lime) (CAS 1305-62-0)	1-5	5 mg/ m <sup>3</sup>	None
Portland Cement (65997-15-1)	30-40	5 mg/ m <sup>3</sup>	None
Calcium Carbonate (1317-65-3)	1-5	5 mg/ m <sup>3</sup>	None
Trade Secret Registry (01664900-5503P)	1-10	N.E.	N.E.

Ingredients not precisely identified are proprietary or nonhazardous. Values are not product specifications. gt = greater than, lt = less than, ca = approximately.

SECTION 3. PHYSICAL DATA

BOILING POINT: No data available. All ingredients have extremely high M.P. & B.P.  
VAPOR PRESSURE (mmHg at 20°C): Not applicable. Solid at all service temperatures.  
VAPOR DENSITY (air = 1): Not applicable.  
pH: No data for this mixture. Ingredients are strongly alkaline when mixed with water.  
SPECIFIC DENSITY: No data for this mixture.  
% VOLATILE BY VOLUME: Not applicable.  
APPEARANCE AND ODOR: Dark gray powdered solid. No particular odor.  
SOLUBILITY IN WATER: Slight.

#### SECTION 4. FIRE AND EXPLOSION DATA

---

FLASH POINT AND METHOD:	Not applicable. Product will not burn.
AUTOIGNITION TEMP.:	Not applicable
FLAMMABLE LIMITS (STP):	Not applicable
EXTINGUISHING MEDIA:	Not applicable
SPECIAL FIRE FIGHTING PROTECTIVE EQUIPMENT:	Not applicable
UNUSUAL FIRE AND EXPLOSION HAZARDS:	None

---

#### SECTION 5. REACTIVITY DATA

---

STABILITY: Stable. Product reacts (hydrates) at a slow, controlled rate when mixed with water releasing minimal heat. Not a hazardous reaction.

##### INCOMPATIBILITY: (MATERIALS TO AVOID)

Strong oxidizing agents such as organic and inorganic acids. Acids will react with cement, lime and carbonates

HAZARDOUS DECOMPOSITION PRODUCTS: None.

HAZARDOUS POLYMERIZATION: Will not occur.

---

#### SECTION 6. HEALTH HAZARD ASSESSMENT

---

GENERAL: No toxicity information is available on this specific preparation; this health hazard assessment is based on information that is available on its components.

INGESTION: No toxic effects are known to be associated with ingestion of this material. May cause irritation to the digestive tract if ingested.

EYE CONTACT: This material can irritate and may burn eyes following direct contact. The aggregate particles may cause abrasions to the cornea.

SKIN CONTACT: Dryness, itching, rashes and burns can develop following contact with skin. Skin abrasions can occur if material is rubbed against the skin. Dermatitis and skin sensitization can develop after repeated and/or prolonged skin contact.

SKIN ABSORPTION: This material is not absorbed through skin contact and no systemically toxic effects are known via this route.

INHALATION: Product contains crystalline quartz ("free") silica. Repeated inhalation of silica in excess of the TLV over extended periods can result in irreversible fibrosis of the lungs (silicosis). Overexposure to dusts can irritate the respiratory tract and can cause damage to the mucous membranes of the upper respiratory tract. IARC has associated high exposure to crystalline silica with cancer in laboratory animals.

OTHER EFFECTS OF OVER EXPOSURE: No other adverse clinical effects are known to be associated with exposure to this material.

##### FIRST AID PROCEDURES

Skin: Rinse skin free of material with water to avoid abrasion of skin. DO NOT RUB until skin is free of material then wash thoroughly with soap and water. If redness, itching, burning or other symptoms develop or persist seek medical attention. Remove and decontaminate clothing and footwear before reuse.

Eyes DO NOT RUB EYES. Rinse immediately with plenty of water. IF symptoms persist consult a physician immediately.

Ingestion: Give one or two glasses of water to drink and refer to medical personnel.

Inhalation: Remove to fresh air. If cough, irritation, difficulty in breathing or other respiratory symptoms persist or develop, consult a physician.

Note to Physician: Mucosal injury following of this material may contraindicate the induction of vomiting in the treatment of possible ingestion.

---

## **SECTION 7. SPILL OR LEAK PROCEDURES**

---

### **STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED OR RELEASED:**

Keep unnecessary people away. Follow personal protection procedures (Section 8) when cleaning up spills. Collect spilled powder by dustless methods and place in containers. If necessary, dike spills of mixed material with absorbent material and shovel into waste containers. Avoid generating dusts. Wet material may be slippery. Use caution to avoid falls.

### **DISPOSAL METHOD:**

Reuse powder or mixed material if uncontaminated. Discard products and hardened mortar are non-hazardous wastes under RCRA (40 CFR, Part 261). Dispose of as nonhazardous waste in compliance with applicable regulations.

### **CONTAINER DISPOSAL:**

Empty container may retain small amounts of residual product. Observe all hazard precautions and personal protection recommendations when handling empty containers. Dispose of as non-hazardous waster in compliance with applicable regulations.

---

## **SECTION 8. SPECIAL PROTECTION INFORMATION**

---

### **TLV OR SUGGESTED CONTROL VALUE:**

No TLV assigned to this mixture. Minimize exposure in accordance with good hygiene practice. (See Sections 2, 10 for TLV's and PEL's).

### **VENTILATION:**

Use local exhaust when possible to keep exposure below applicable exposure limits for silica, portland cement, and nuisance dusts.

### **RESPIRATORY PROTECTION (SPECIFY TYPE):**

Where exposure to dusts from this product may exceed the applicable exposure limits a MSHA-NIOSH approved respirator for the dust should be used.

### **PROTECTIVE CLOTHING:**

Gloves and protective clothing recommended to avoid skin contact.

### **EYE PROTECTION:**

Full face-shield or chemical tight goggles recommended to avoid splashing in eyes while handling, mixing, placing or as long as splash hazard exists. Safety glasses recommended if grinding, cutting, etc. of hardened material is required.

### **OTHER PROTECTIVE EQUIPMENT:**

Provide eyewash station or other suitable means of cleansing eyes and skin in emergencies.

---

## **SECTION 9. SPECIAL PRECAUTIONS OR OTHER COMMENTS**

---

### **PRECAUTIONS TO BE TAKEN IN HANDLING OR STORING:**

Store in cool dry area off ground. Avoid contact with acids and other oxidizers. Minimize generation of dusts. Avoid skin and eye contact. Avoid breathing dusts. A sensitized individual should not be exposed to the product which causes sensitization.

## SECTION 10. MISCELLANEOUS INFORMATION

---

### FOOTNOTES:

(a) Source: Threshold Limit Values and Biological Exposure Indices for 1987-88., American Conference of Governmental Industrial Hygienists, Cincinnati, OH 45211.

(b) PEL for silica, crystalline quartz:

For respirable dust in  $\text{mg}/\text{m}^3$ :  $\frac{10 \text{ mg}/\text{m}^3}{\% \text{ SiO}_2 + 2}$

For total dust in  $\text{mg}/\text{m}^3$ :  $\frac{30 \text{ mg}/\text{m}^3}{\% \text{ SiO}_2 + 2}$