



Add a Pak SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

PRODUCT NAME: Add A Pak
Recommended Use: Architectural coating material
Restriction on Use: Use only as directed

MANUFACTURER: Merlex Stucco, Inc.
ADDRESS: 2911 Orange-Olive Rd.
Orange, CA 92665

Phone: 1-714-637-1700

Fax: 1-714-637-4865

Website: www.merlex.com

SDS Date of Preparation: April 7, 2015

SECTION 2. HAZARD(S) IDENTIFICATION

US GHS Classification:

Physical	Health
Not Hazardous	Specific Target Organ Toxicity Repeat Exposure Category 1 Carcinogen Category 1A

Labeling Elements:
Danger!



Hazard statement(s)

May cause cancer by inhalation.
Causes damage to lungs through prolonged or repeated exposure by inhalation.

Precautionary statement(s)

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not breathe dust.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
In case of inadequate ventilation wear respiratory protection.
IF exposed or concerned: Get medical attention.
Store locked up.
Dispose of contents and container in accordance with local and national regulations.

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

Component	CAS No.	Conc in %
Iron Oxide Pigments	1309-37-1, 1332-37-2	1-100%
Calcium Carbonate (Limestone)	1317-65-3	1-99%
Crystalline Silica, Quartz	14808-60-7	0.1-1%

The specific identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4. FIRST AID MEASURES

Ingestion: Wash mouth with water. Do not induce vomiting. Seek immediate medical attention.

Skin Contact: Remove contaminated clothing and wash with plenty of soap and water. Get medical attention if irritation or other symptoms develop. Launder contaminated clothing before reuse.

Eye Contact: Rinse immediately with plenty of water for 15 minutes, while lifting the eyelids. Get immediate medical attention.

Inhalation: Remove affected person from source of exposure. If symptoms of exposure persist, get medical attention.

Most important symptoms/effects, acute and delayed: May cause eye and skin irritation. Inhalation of dust may cause irritation of the nose, throat and respiratory tract. Prolonged overexposure to respirable crystalline silica may cause lung disease (silicosis) and increase the risk of lung cancer. Risk of cancer depends on duration and level of exposure.

Indication of immediate medical attention and special treatment, if necessary: Immediate medical attention is not required.

SECTION 5. FIRE FIGHTING MEASURES

Suitable (and unsuitable) extinguishing media: Use any extinguishing media that is appropriate for the surrounding fire.

Specific hazards arising from the chemical: This product is not combustible. Thermal decomposition may generate oxides of iron, calcium and carbon.

Special protective equipment and precautions for fire-fighters: Firefighters should always wear positive pressure self-contained breathing apparatus and protective clothing when fighting fires involving chemicals.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures: Wear appropriate protective clothing to avoid eye and skin contact.

Environmental hazards: Report spills and releases as required to appropriate authorities.

Methods and materials for containment and cleaning up: Carefully collect dry material. Avoid creating airborne dust. Scrape up wet product. Place into an appropriate container for re-use or disposal.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling: Do not breathe dust. Avoid contact with the eyes, skin and clothing. Wear appropriate protective clothing and equipment handling this material. Wash thoroughly after handling. Immediately remove contaminated clothing and launder before re-use. Do not eat, drink or smoke in the work area. Keep product dry until use.

Empty containers may contain product residue and may be hazardous. Follow all SDS precautions in handling empty containers.

Conditions for safe storage: Store in cool, dry area.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION INFORMATION

Exposure Limits

Chemical Name	Exposure Limits
Iron Oxide Pigments	10 mg/m ³ TWA OSHA PEL (as iron oxide fume) 5 mg/m ³ TWA ACGIH TLV (respirable)
Calcium Carbonate	10 mg/m ³ ACGIH TLV-TWA (total dust) 5 mg/m ³ OSHA PEL-TWA (respirable dust) 15 mg/m ³ OSHA PEL-TWA (total dust)
Crystalline Silica, Quartz	10 mg/m ³ TWA OSHA PEL (respirable fraction) % Silica + 2 30 mg/m ³ TWA OSHA PEL (total dust) % Silica + 2 0.025 mg/m ³ TWA ACGIH TLV (respirable fraction)

Appropriate engineering controls: Use with adequate general or local exhaust ventilation to maintain exposures below applicable occupational exposure limits.

Individual protection measures, such as personal protective equipment:

Respiratory Protection: If needed, a NIOSH approved respirator with dust cartridges (N95/P95 or N100/P100) may be used. For higher exposures, a supplied air respirator may be required. Selection of respiratory protection depends on the contaminant type, form and concentration. Select in accordance with OSHA 1910.134 and good Industrial Hygiene practice.

Skin Protection: Avoid prolonged skin contact. Wear impervious gloves if needed to avoid contact.

Eye Protection: Safety glasses or goggles recommended.

Other: Impervious clothing as needed to avoid contamination of personal clothing. An eye wash should be available in the immediate work area.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Fine powdered solid, various colors.

Odor: No odor.

Odor threshold: Not available	pH: Not available
Melting point/freezing point: Not applicable	Boiling point: Not applicable
Flash point: Not Applicable	Evaporation rate: Not applicable
Flammability (solid, gas): Not applicable	
Flammable limits: LEL: Not applicable	UEL: Not applicable
Vapor pressure: Not applicable	Vapor density: Not applicable
Relative density: Not available	Solubility: Slightly in Water
Partition coefficient: n-octanol/water: Not applicable	Auto-ignition temperature: Not applicable
Decomposition temperature: Not applicable	Viscosity: Not applicable

SECTION 10. STABILITY AND REACTIVITY DATA

Reactivity: Not reactive under normal conditions of use.

Chemical stability: Stable under normal conditions of use and storage.

Possibility of hazardous reactions: Crystalline silica will dissolve in hydrofluoric acid and produce silicone tetrafluoride. Reacts with acids producing carbon dioxide.

Conditions to avoid: Avoid contact with water or moisture until use.

Incompatible materials: Strong acids, ammonium salts and aluminum metal.

Hazardous decomposition products: Thermal decomposition may generate oxides of iron, calcium and carbon.

SECTION 11. TOXICOLOGICAL INFORMATION

PRODUCT HEALTH HAZARD INFORMATION

Skin: Contact with dry product may cause dryness of the skin. Contact with wet product or presence of product on skin damp with sweat may cause irritation.

Eye: May cause irritation. Dust may cause physical (mechanical) eye injury.

Inhalation: May cause irritation of the nose, throat and upper respiratory tract.

Ingestion: May cause irritation of the mouth and gastrointestinal tract.

Chronic Health Effects: Chronic overexposure to any respirable dust will cause adverse effects on the lung. Prolonged overexposure to iron oxide may result in a benign lung condition called siderosis. This product may contain trace amounts of naturally occurring crystalline silica. Chronic overexposure to respirable crystalline silica may cause a progressive, disabling lung disease, silicosis which may be fatal. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness and reduced pulmonary function. This disease is exacerbated by smoking. The International Agency for Research on Cancer (IARC) has determined that crystalline silica inhaled in the form of quartz is carcinogenic to humans (Group 1). The National Toxicology Program classifies respirable crystalline silica as known to be a human carcinogen. The American Conference of Governmental Industrial Hygienists (ACGIH) classifies crystalline silica, quartz, as a suspected human carcinogen (A2).

Acute Toxicity Values

Crystalline Silica, Quartz: Oral rat LD50 >22,500 mg/kg

Iron Oxide Pigments: Oral; rat LD50 >10000 mg/kg

Calcium Carbonate: Oral rat LD50 >2000 mg/kg, Inhalation rat LC50 >3 mg/L/4 hr, (no mortality occurred),

Dermal rat LD50 >2000 mg/kg (structurally similar chemical)

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity:

Iron Oxide Pigments: 96 hr LC0 >50000 mg/L, 48 hr EC50 daphnia magna >100 mg/L

Calcium Carbonate: 96 hr LC50 *Oncorhynchus mykiss* >100 mg/L, 48 hr EC50 daphnia magna >100 mg/L, 72 hr EC50 *Desmodesmus subspicatus* >140 mg/L (structurally similar chemical)

Crystalline Silica: 72 hr LC50 carp >10,000 mg/L

Persistence and degradability: Biodegradation is not applicable to inorganic substances.

Bioaccumulative potential: Not expected to be bioaccumulative

Mobility in soil: No data available.

Other adverse effects: None known

SECTION 13. DISPOSAL CONSIDERATIONS

Dispose in accordance with all local, state and federal regulations.

SECTION 14. TRANSPORT INFORMATION

	UN Number	Proper shipping name	Hazard Class	Packing Group	Environmental Hazard
DOT		Not Regulated			

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not applicable – product is transported only in packaged form.

Special precautions: None known.

SECTION 15. REGULATORY INFORMATION

SARA TITLE III INFORMATION:

Section 311/312 (40 CFR 370) Hazard Categories: Acute Health

Section 313 (40 CFR 372): This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirement: None

Section 302 (40 CFR 355): This product does not contain chemicals listed as extremely hazardous chemicals under SUPERFUND Amendments and Reauthorization Act (SARA).

CERCLA Hazardous Substances (Section 103)/RQ: This product is not subject to CERCLA reporting requirements as it is sold. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

EPA TSCA: All of the components of this product are listed on the EPA TSCA Inventory.

California Proposition 65: This product may contain trace amounts of respirable crystalline silica, which is known to the State of California to cause cancer.

SECTION 16. OTHER INFORMATION

NFPA Hazard Rating: Health: 1 Fire: 0 Reactivity: 0

HMS Hazard Rating: Health: 1 Fire: 0 Reactivity: 0

SDS Revision History: All Sections revised – Updated to GHS format.

Date of preparation: April 7, 2015

Date of last revision: November 29, 2004

NOTICE: The information presented herein is based on data considered to be accurate as of the date of preparation of this Material Safety Data Sheet. However, no warranty or representation, express or implied, is made as to the accuracy or completeness of the foregoing data and safety information. It is the responsibility of the user to determine the applicability of this information for his use.